

Belgravia 3/4" Thermostatic Valve Trim with Crosshead and Lever Handles

US-BL2000R

FEATURES


- Thermostatic valve trim with crosshead and white porcelain lever handles
- 2 integrated volume controls for 2 water outlets
- Vernet thermostatic cartridge and Fluhs flow control cartridge
- Cartridge restricts water supply should the hot or cold supply fail, to prevent scalding or thermal shock
- Integral shut-off non-return valves with filters to prevent cross flow
- Built-in service stops
- Available finishes:
 - US-BL2000RC_LV - Polished chrome
 - US-BL2000RN_LV - Polished nickel
- Required rough (sold separately):
 - US-WLBP2000R



SPECIFICATION

- Flow rate: 13 gpm at 60 psi
- Water pressure maximum: Operating pressure of 60psi and static pressure of 144 psi
- Water pressure minimum: 20 psi
- Inlet connection: 3/4" NPT
- Outlet connection: 3/4" NPT
- Rough-in depth minimum: 2-15/16"
- Rough-in depth maximum: 4-1/8"
- Handle style: Crosshead (mixer), white porcelain lever (volume controls)
- Extension kit:
 - US-EK2000C Polished chrome
 - US-EK2000N Polished nickel
- Material: Brass
- Warranty: Limited lifetime
- Commercial: 1 year

2 function, shared



A: Independent Water Control
B: Temperature
C: Independent Water Control

CERTIFICATIONS

- Meets or exceeds ASME A112.18.1 / IAPMO Z124 / CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts, and others
- Code compliance: ADA, UPC, cUPC
- ADA compliant

