

Belgravia 3/4" Thermostatic Valve Trim with Crosshead Handles

US-BL2500R

FEATURES


- Thermostatic valve trim with metal cross-head handles
- Single integrated volume control/3-way diverter for 3 water outlets
- Vernet thermostatic cartridge
- Cartridge restricts water supply should the hot or cold supply fail, to prevent scalding or thermal shock
- Integral shut-off non-return valves with filters to prevent cross flow
- Built-in service stops
- Available finishes:
 - US-BL2500RC - Polished chrome
 - US-BL2500RN - Polished nickel
- Required rough (sold separately):
 - US-WLBP2500R



3 function, non-shared

SPECIFICATION

- Flow rate: 12 gpm at 60 psi
- Water pressure maximum: Operating pressure of 60psi and static pressure of 144 psi
- Water pressure minimum: 20 psi
- Inlet connection: 3/4" NPT
- Outlet connection: 3/4" NPT
- Rough-in depth minimum: 3"
- Rough-in depth maximum: 3-7/8"
- Material: Brass
- Handle style: Crosshead
- Extension kit:
 - US-EK10125C Polished chrome
 - US-EK10125N Polished nickel
- Warranty: Limited lifetime
Commercial: 1 year



A: Water Control / 3 Way Diverter
B: Temperature

CERTIFICATIONS

- Meets or exceeds ASME A112.18.1 / IAPMO Z124 / CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts, and others
- Code compliance: ADA, UPC, cUPC
- ADA compliant

